


1506R

VINYL SEAL TAPE

VentureTape® 1506R is a 5 mil white vinyl seal tape coated with an aggressive rubber pressure sensitive adhesive (PSA) specifically designed to adhere to PVC fittings. Resistant to moisture, acids, alkalis, oils and other chemicals as well as highly abrasion resistant, VentureTape 1506R is ideal for use on PVC jacketing and fittings.

Product Construction



Features & Benefits

- Primarily used in the application of pre-molded high impact PVC insulation fitting covers
- Conformable, high performance vinyl seal tape performs well over a wide temperature range
- Color matched specifically for PVC
- For interior use.
- High tack rubber based adhesive.

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness ^Ω	6.0 mils	0.15 mm	PSTC-133
Peel Adhesion ^Δ	29 oz/in	8.1 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	15 lb/in	67.8 N/25 mm	PSTC-131
Elongation	150 %	150 %	PSTC-131
Service Temperature	0 to 175 °F	-18 to 79 °C	

^Ω - excluding liner

^Δ - 20 minute dwell

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Product Configurations

- Available in Black or White
- Standard widths: 1", 1 ½", and 2"
- Standard length: 36Y

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076

From United Kingdom 0-800-962-957

From Australia 1-800-122-797

www.venturetape.com

VentureTape®

GTA - NHT, Inc.
Venture Tape
30 Commerce Rd., Rockland, MA 02370
Tel 781-331-5900; Fax 781-871-0065
800-343-1076 (U.S.A.), 800-544-1024 (Canada)
Toll Free Fax 877-264-5490
www.venturetape.com

GTA
TAPES & ADHESIVES
a 3M Company